



TPECP 40000 - ON REQUEST THREE-PHASE TRANSFORMER ECO-DESIGN A0AK 40KVA - IP21



SKU: TPECP40000_Specific
Référence technique: A67B49...



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 40 kVA
Primary voltage : max. 1000V
Secondary voltage : max. 1000V
:
Protection : IP21-IK08
Version : Transformer (energy savings ECO DESIGN A0Ak - specific)
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 40°C
No load losses : 155 W
Load losses : 1340 W
Voltage drop : 3,2 %
UCC : 4,1 %
Efficiency : 96,4 %

DIMENSIONS:

Dimensions (A x B x H) : 610 x 470 x 770 mm
Mounting centres (a x b) : 395 x 440 mm
Mounting diameter (Ø) : 11 x 22 mm
Weight : 179 kg

PROTECTION(S) RECOMMANDÉE(S):

:
Other voltages : N.C.

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization
Vibration isolating mount
Running wheels
Factory assembled and wired primary and secondary protections
Specific colour for the enclosure