




## TPECP 40000 - ON REQUEST THREE-PHASE TRANSFORMER ECO-DESIGN A0AK 40KVA - IP21



SKU: TPECP40000\_Specific  
Référence technique: A67B49...

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 40 kVA  
Primary voltage : max. 1000V  
Secondary voltage : max. 1000V  
:  
Protection : IP21-IK08  
Version : Transformer (energy savings ECO DESIGN A0Ak - specific)  
Inrush current : less than or equal to 7 In  
Heatings : H (IEC 60085)  
Max. ambient T° : 40°C  
No load losses : 155 W  
Load losses : 1340 W  
Voltage drop : 3,2 %  
UCC : 4,1 %  
Efficiency : 96,4 %

### DIMENSIONS:

Dimensions (A x B x H) : 610 x 470 x 770 mm  
Mounting centres (a x b) : 395 x 440 mm  
Mounting diameter (Ø) : 11 x 22 mm  
Weight : 179 kg

### PROTECTION(S) RECOMMANDÉE(S):

:  
Other voltages : N.C.

### OPTIONS:

Electrostatic shield  
Thermal sensors (PTC, PT100, Twin-blades)  
Regulation tabs  
Primary and/or secondary coupling (star, delta, zig-zag)  
Dual primary  
Inrush current, frequency, heating, ambient temperature, specific altitude  
Tropicalization  
Vibration isolating mount  
Running wheels  
Factory assembled and wired primary and secondary protections  
Specific colour for the enclosure