



TPECP 63000 - THREE-PHASE TRANSFORMER ECO-DESIGN A0AK 400/230V - 63KVA - IP21



SKU: 36515
 Référence technique: A67B51FD00000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 60076
 Power : 63 kVA
 Primary voltage : 400V
 Secondary voltage : 230V (Y+N)
 :
 Protection : IP21-IK08
 Version : économies d'énergie ECO DESIGN A0Ak
 Inrush current : less than or equal to 7 In
 Heatings : H (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 195 W
 Load losses : 1560 W
 Voltage drop : 2,4 %
 UCC : 4,7 %
 Efficiency : 97,3 %

DIMENSIONS:

Dimensions (A x B x H) : 800 x 520 x 980 mm
 Mounting centres (a x b) : 570 x 490 mm
 Mounting diameter (Ø) : 11 x 22 mm
 Weight : 360 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 100A
 :
 Secondary 230V (gG fuse(s)) : 4 x 160A
 Secondary 230V (C circuit breaker(s)) : 4 x 160A

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Primary and/or secondary coupling (star, delta, zig-zag)
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization
 Vibration isolating mount
 Running wheels
 Factory assembled and wired primary and secondary protections

Specific colour for the enclosure