



TPECP 630000 - THREE-PHASE TRANSFORMER ECO-DESIGN A0AK 400/230V - 630KVA - IP21



SKU: 36615
Référence technique: S67B61FD00000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 630 kVA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP21-IK08
Version : économies d'énergie ECO DESIGN A0Ak
Inrush current : less than or equal to 7 In
Heatings : H (IEC 60085)
Max. ambient T° : 35°C
No load losses : 990 W
Load losses : 7100 W
Voltage drop : 1,1 %
UCC : 3,2 %
Efficiency : 98,7 %

DIMENSIONS:

Dimensions (A x B x H) : 1450 x 1200 x 1450 mm
Mounting centres (a x b) : 920 x 1150 mm
Mounting diameter (Ø) : 14 mm
Weight : 2005 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 1000A
:

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization
Vibration isolating mount
Running wheels
Factory assembled and wired primary and secondary protections
Specific colour for the enclosure