



TPP 100 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - 100VA - IP21



SKU: 31187
 Référence technique: 29M18FFF0000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 100 VA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP41-IK08
 Version : with regulation tabs $\pm 5\%$
 Inrush current : less than or equal to 25 In
 Heatings : B (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 4,1 W
 Load losses : 14,3 W
 Voltage drop : 12,5 %
 UCC : 10,5 %
 Efficiency : 84,5 %

DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm
 Mounting centres (a x b) : 200 x 224 mm
 Mounting diameter (\emptyset) : 7x14 mm
 Weight : 4,6 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 0,5A
 :
 Secondary 400V (gG fuse(s)) : 4 x 0,16A

OPTIONS:

Tropicalization
 Specific colour for the enclosure