




## TPP 1600 - THREE-PHASE TRANSFORMER 400/400V - ELECTROSTATIC SHIELD - 1600VA - IP21



SKU: 31346  
Référence technique: 29M34FF01000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 1600 VA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP41-IK08  
Version : with electrostatic shield  
Inrush current : less than or equal to 25 In  
Heatings : F (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 39 W  
Load losses : 103 W  
Voltage drop : 6,1 %  
UCC : 4,5 %  
Efficiency : 91,8 %

### DIMENSIONS:

Dimensions (A x B x H) : 300 x 290 x 300 mm  
Mounting centres (a x b) : 250 x 274 mm  
Mounting diameter (ø) : 7x14 mm  
Weight : 21,1 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 5A  
:  
Secondary 400V (gG fuse(s)) : 4 x 2,5A  
Secondary 400V (C circuit breaker(s)) : 4 x 2,5A

### OPTIONS:

Tropicalization  
Specific colour for the enclosure