




TPP 1600 - THREE-PHASE TRANSFORMER 400/230V - 1600VA - IP21



SKU: 32345
Référence technique: 29M34FD00000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 1600 VA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP41-IK08
Version : standard
Inrush current : less than or equal to 25 In
Heatings : F (IEC 60085)
Max. ambient T° : 35°C
No load losses : 39 W
Load losses : 103 W
Voltage drop : 6,1 %
UCC : 4,5 %
Efficiency : 91,8 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 290 x 300 mm
Mounting centres (a x b) : 250 x 274 mm
Mounting diameter (ø) : 7x14 mm
Weight : 21,1 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 5A
:
Secondary 230V (gG fuse(s)) : 4 x 4A
Secondary 230V (C circuit breaker(s)) : 4 x 4A

OPTIONS:

Tropicalization
Specific colour for the enclosure