




TPP 1600 - ON REQUEST THREE-PHASE TRANSFORMER 1600VA - IP21



SKU: TPP1600_Specific
Référence technique: 29M34...

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 1600 VA
Primary voltage : max. 1000V
Secondary voltage : max. 1000V
:
Protection : IP41-IK08
Version : specific
Inrush current : less than or equal to 25 In
Heatings : F (IEC 60085)
Max. ambient T° : 35°C
No load losses : 39 W
Load losses : 103 W
Voltage drop : 6,1 %
UCC : 4,5 %
Efficiency : 91,8 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 290 x 300 mm
Mounting centres (a x b) : 250 x 274 mm
Mounting diameter (ø) : 7x14 mm
Weight : 21,1 kg

PROTECTION(S) RECOMMANDÉE(S):

:
Other voltages : N.C.

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization
Specific colour for the enclosure