



TPP 2000 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - 2KVA - IP21



SKU: 31357
 Référence technique: 29M35FFF0000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 2 kVA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP41-IK08
 Version : with regulation tabs $\pm 5\%$
 Inrush current : less than or equal to 25 In
 Heatings : F (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 47 W
 Load losses : 112 W
 Voltage drop : 5,3 %
 UCC : 3,9 %
 Efficiency : 92,6 %

DIMENSIONS:

Dimensions (A x B x H) : 300 x 290 x 300 mm
 Mounting centres (a x b) : 250 x 274 mm
 Mounting diameter (\emptyset) : 7x14 mm
 Weight : 24,1 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 6,3A
 :
 Secondary 400V (gG fuse(s)) : 4 x 3,15A
 Secondary 400V (C circuit breaker(s)) : 4 x 3,15A

OPTIONS:

Tropicalization
 Specific colour for the enclosure