




TPP 200 - ON REQUEST THREE-PHASE TRANSFORMER 200VA - IP21



SKU: TPP200_Specific
Référence technique: 29M22...

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 200 VA
Primary voltage : max. 1000V
Secondary voltage : max. 1000V
:
Protection : IP41-IK08
Version : specific
Inrush current : less than or equal to 25 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 7,8 W
Load losses : 20,9 W
Voltage drop : 9,5 %
UCC : 7,9 %
Efficiency : 87,5 %

DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm
Mounting centres (a x b) : 200 x 224 mm
Mounting diameter (ø) : 7x14 mm
Weight : 6,3 kg

PROTECTION(S) RECOMMANDÉE(S):

:
Other voltages : N.C.

OPTIONS:

Electrostatic shield
Thermal sensors (PTC, PT100, Twin-blades)
Regulation tabs
Primary and/or secondary coupling (star, delta, zig-zag)
Dual primary
Inrush current, frequency, heating, ambient temperature, specific altitude
Tropicalization
Specific colour for the enclosure