



## TPP 2500 - THREE-PHASE TRANSFORMER 400/230V - 2,5KVA - IP21



SKU: 32365  
Référence technique: 29M36FD00000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 2,5 kVA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP21-IK08  
Version : standard  
Inrush current : less than or equal to 25 In  
Heatings : F (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 59 W  
Load losses : 114 W  
Voltage drop : 4,4 %  
UCC : 3,2 %  
Efficiency : 93,5 %

### DIMENSIONS:

Dimensions (A x B x H) : 380 x 370 x 530 mm  
Mounting centres (a x b) : 200 x 340 mm  
Mounting diameter (ø) : 11x22 mm  
Weight : 35 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 8A  
:  
Secondary 230V (gG fuse(s)) : 4 x 6A  
Secondary 230V (C circuit breaker(s)) : 4 x 6A

### OPTIONS:

Tropicalization  
Specific colour for the enclosure