






TPP 315 - THREE-PHASE TRANSFORMER 400/400V - ELECTROSTATIC SHIELD - 315VA - IP21



SKU: 31246
Référence technique: 29M25FF01000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 315 VA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP41-IK08
Version : with electrostatic shield
Inrush current : less than or equal to 25 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 12,5 W
Load losses : 26,3 W
Voltage drop : 7,7 %
UCC : 6,4 %
Efficiency : 89,1 %

DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm
Mounting centres (a x b) : 200 x 224 mm
Mounting diameter (∅) : 7x14 mm
Weight : 8,3 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 1A
:
Secondary 400V (gG fuse(s)) : 4 x 0,5A

OPTIONS:

Tropicalization
Specific colour for the enclosure