



## TPP 315 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - 315VA - IP21



SKU: 31247  
Référence technique: 29M25FFF0000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 315 VA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP41-IK08  
Version : with regulation tabs  $\pm 5\%$   
Inrush current : less than or equal to 25 In  
Heatings : B (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 12,5 W  
Load losses : 26,3 W  
Voltage drop : 7,7 %  
UCC : 6,4 %  
Efficiency : 89,1 %

### DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm  
Mounting centres (a x b) : 200 x 224 mm  
Mounting diameter ( $\emptyset$ ) : 7x14 mm  
Weight : 8,3 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 1A  
:  
Secondary 400V (gG fuse(s)) : 4 x 0,5A

### OPTIONS:

Tropicalization  
Specific colour for the enclosure