



## TPP 315 - THREE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - ELECTROSTATIC SHIELD - 315VA - IP21



SKU: 32248  
 Référence technique: 29M25FDF1000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 61558-2-1  
 Power : 315 VA  
 Primary voltage : 400V  
 Secondary voltage : 230V (Y+N)  
 :  
 Protection : IP41-IK08  
 Version : with electrostatic shield & regulation tabs  $\pm 5\%$   
 Inrush current : less than or equal to 25 In  
 Heatings : B (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 12,5 W  
 Load losses : 26,3 W  
 Voltage drop : 7,7 %  
 UCC : 6,4 %  
 Efficiency : 89,1 %

### DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm  
 Mounting centres (a x b) : 200 x 224 mm  
 Mounting diameter ( $\emptyset$ ) : 7x14 mm  
 Weight : 8,3 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 1A  
 :  
 Secondary 230V (gG fuse(s)) : 4 x 0,8A

### OPTIONS:

Tropicalization  
 Specific colour for the enclosure