



**TPP 3150 - THREE-PHASE  
TRANSFORMER 400/400V  $\pm 5\%$  -  
ELECTROSTATIC SHIELD - 3,15KVA -  
IP21**



SKU: 31388

Référence technique: 29M38FFF1000

### **CARACTÉRISTIQUES TECHNIQUES:**

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 3,15 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP21-IK08  
Version : with electrostatic shield & regulation tabs  $\pm 5\%$   
Inrush current : less than or equal to 25  $I_n$   
Heatings : F (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 73 W  
Load losses : 151 W  
Voltage drop : 4,6 %  
UCC : 3,4 %  
Efficiency : 93,4 %

### **DIMENSIONS:**

Dimensions (A x B x H) : 380 x 370 x 530 mm  
Mounting centres (a x b) : 250 x 340 mm  
Mounting diameter ( $\varnothing$ ) : 11x22 mm  
Weight : 41 kg

### **PROTECTION(S) RECOMMANDÉE(S):**

Primary 400V (aM fuse(s)) : 3 x 10A  
:  
Secondary 400V (gG fuse(s)) : 4 x 5A  
Secondary 400V (C circuit breaker(s)) : 4 x 5A

### **OPTIONS:**

Tropicalization  
Specific colour for the enclosure