




**TPP 3150 - THREE-PHASE
 TRANSFORMER 400/400V ±5% -
 ELECTROSTATIC SHIELD - 3,15KVA -
 IP21**



SKU: 31388
 Référence technique: 29M38FFF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 3,15 kVA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP21-IK08
 Version : with electrostatic shield & regulation tabs ±5%
 Inrush current : less than or equal to 25 I_n
 Heatings : F (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 73 W
 Load losses : 151 W
 Voltage drop : 4,6 %
 UCC : 3,4 %
 Efficiency : 93,4 %

DIMENSIONS:

Dimensions (A x B x H) : 380 x 370 x 530 mm
 Mounting centres (a x b) : 250 x 340 mm
 Mounting diameter (Ø) : 11x22 mm
 Weight : 41 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 10A
 :
 Secondary 400V (gG fuse(s)) : 4 x 5A
 Secondary 400V (C circuit breaker(s)) : 4 x 5A

OPTIONS:

Tropicalization
 Specific colour for the enclosure