



## TPP 3150 - ON REQUEST THREE-PHASE TRANSFORMER 3,15KVA - IP21



SKU: TPP3150\_Specific  
 Référence technique: 29M38...



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 61558-2-1  
 Power : 3,15 kVA  
 Primary voltage : max. 1000V  
 Secondary voltage : max. 1000V  
 :  
 Protection : IP21-IK08  
 Version : specific  
 Inrush current : less than or equal to 25 In  
 Heatings : F (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 73 W  
 Load losses : 151 W  
 Voltage drop : 4,6 %  
 UCC : 3,4 %  
 Efficiency : 93,4 %

### DIMENSIONS:

Dimensions (A x B x H) : 380 x 370 x 530 mm  
 Mounting centres (a x b) : 250 x 340 mm  
 Mounting diameter (ø) : 11x22 mm  
 Weight : 41 kg

### PROTECTION(S) RECOMMANDÉE(S):

:  
 Other voltages : N.C.

### OPTIONS:

Electrostatic shield  
 Thermal sensors (PTC, PT100, Twin-blades)  
 Regulation tabs  
 Primary and/or secondary coupling (star, delta, zig-zag)  
 Dual primary  
 Inrush current, frequency, heating, ambient temperature, specific altitude  
 Tropicalization  
 Specific colour for the enclosure