




TPP 3150 - ON REQUEST THREE-PHASE TRANSFORMER 3,15KVA - IP21



SKU: TPP3150_Specific
 Référence technique: 29M38...



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 3,15 kVA
 Primary voltage : max. 1000V
 Secondary voltage : max. 1000V
 :
 Protection : IP21-IK08
 Version : specific
 Inrush current : less than or equal to 25 In
 Heatings : F (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 73 W
 Load losses : 151 W
 Voltage drop : 4,6 %
 UCC : 3,4 %
 Efficiency : 93,4 %

DIMENSIONS:

Dimensions (A x B x H) : 380 x 370 x 530 mm
 Mounting centres (a x b) : 250 x 340 mm
 Mounting diameter (ø) : 11x22 mm
 Weight : 41 kg

PROTECTION(S) RECOMMANDÉE(S):

:
 Other voltages : N.C.

OPTIONS:

Electrostatic shield
 Thermal sensors (PTC, PT100, Twin-blades)
 Regulation tabs
 Primary and/or secondary coupling (star, delta, zig-zag)
 Dual primary
 Inrush current, frequency, heating, ambient temperature, specific altitude
 Tropicalization
 Specific colour for the enclosure