




**TPP 400 - THREE-PHASE  
TRANSFORMER 400/400V ±5% -  
ELECTROSTATIC SHIELD - 400VA - IP21**



SKU: 31268  
Référence technique: 29M26FFF1000



### **CARACTÉRISTIQUES TECHNIQUES:**

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 400 VA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP41-IK08  
Version : with electrostatic shield & regulation tabs ±5%  
Inrush current : less than or equal to 25 In  
Heatings : B (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 13,1 W  
Load losses : 33,6 W  
Voltage drop : 7,7 %  
UCC : 6,4 %  
Efficiency : 89,5 %

### **DIMENSIONS:**

Dimensions (A x B x H) : 250 x 240 x 220 mm  
Mounting centres (a x b) : 200 x 224 mm  
Mounting diameter (ø) : 7x14 mm  
Weight : 9,4 kg

### **PROTECTION(S) RECOMMANDÉE(S):**

Primary 400V (aM fuse(s)) : 3 x 0,25A  
:  
Secondary 400V (gG fuse(s)) : 4 x 0,63A

### **OPTIONS:**

Tropicalization  
Specific colour for the enclosure