




**TPP 400 - THREE-PHASE
 TRANSFORMER 400/230V ±5% -
 ELECTROSTATIC SHIELD - 400VA - IP21**



SKU: 32268
 Référence technique: 29M26FDF1000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 400 VA
 Primary voltage : 400V
 Secondary voltage : 230V (Y+N)
 :
 Protection : IP41-IK08
 Version : with electrostatic shield & regulation tabs ±5%
 Inrush current : less than or equal to 25 In
 Heatings : B (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 13,1 W
 Load losses : 33,6 W
 Voltage drop : 7,7 %
 UCC : 6,4 %
 Efficiency : 89,5 %

DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm
 Mounting centres (a x b) : 200 x 224 mm
 Mounting diameter (ø) : 7x14 mm
 Weight : 9,4 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 0,25A
 :
 Secondary 230V (gG fuse(s)) : 4 x 1A
 Secondary 230V (C circuit breaker(s)) : 4 x 1A

OPTIONS:

Tropicalization
 Specific colour for the enclosure