




TPP 4000 - THREE-PHASE TRANSFORMER 400/230V - ELECTROSTATIC SHIELD - 4KVA - IP21



SKU: 32396
 Référence technique: 29M39FD01000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 4 kVA
 Primary voltage : 400V
 Secondary voltage : 230V (Y+N)
 :
 Protection : IP21-IK08
 Version : with electrostatic shield
 Inrush current : less than or equal to 25 In
 Heatings : F (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 85 W
 Load losses : 161 W
 Voltage drop : 3,9 %
 UCC : 2,9 %
 Efficiency : 94,2 %

DIMENSIONS:

Dimensions (A x B x H) : 380 x 370 x 530 mm
 Mounting centres (a x b) : 250 x 340 mm
 Mounting diameter (ø) : 11x22 mm
 Weight : 47 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 12A
 :
 Secondary 230V (gG fuse(s)) : 4 x 10A
 Secondary 230V (C circuit breaker(s)) : 4 x 10A

OPTIONS:

Tropicalization
 Specific colour for the enclosure