




TPP 500 - THREE-PHASE TRANSFORMER 400/400V - ELECTROSTATIC SHIELD - 500VA - IP21



SKU: 31276
 Référence technique: 29M27FF01000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
 Current : three-phase
 Certification(s) : EN 61558-2-1
 Power : 500 VA
 Primary voltage : 400V
 Secondary voltage : 400V (Y+N)
 :
 Protection : IP41-IK08
 Version : with electrostatic shield
 Inrush current : less than or equal to 25 In
 Heatings : B (IEC 60085)
 Max. ambient T° : 35°C
 No load losses : 15,3 W
 Load losses : 40,3 W
 Voltage drop : 7,45 %
 UCC : 6,3 %
 Efficiency : 90 %

DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm
 Mounting centres (a x b) : 200 x 224 mm
 Mounting diameter (ø) : 7x14 mm
 Weight : 10,1 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 1,6A
 :
 Secondary 400V (gG fuse(s)) : 4 x 0,8A

OPTIONS:

Tropicalization
 Specific colour for the enclosure