




## TPP 500 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - ELECTROSTATIC SHIELD - 500VA - IP21



SKU: 31278  
 Référence technique: 29M27FFF1000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 61558-2-1  
 Power : 500 VA  
 Primary voltage : 400V  
 Secondary voltage : 400V (Y+N)  
 :  
 Protection : IP41-IK08  
 Version : with electrostatic shield & regulation tabs  $\pm 5\%$   
 Inrush current : less than or equal to 25 In  
 Heatings : B (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 15,3 W  
 Load losses : 40,3 W  
 Voltage drop : 7,45 %  
 UCC : 6,3 %  
 Efficiency : 90 %

### DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm  
 Mounting centres (a x b) : 200 x 224 mm  
 Mounting diameter ( $\emptyset$ ) : 7x14 mm  
 Weight : 10,1 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 1,6A  
 :  
 Secondary 400V (gG fuse(s)) : 4 x 0,8A

### OPTIONS:

Tropicalization  
 Specific colour for the enclosure