



## TPP 500 - THREE-PHASE TRANSFORMER 400/230V $\pm 5\%$ - ELECTROSTATIC SHIELD - 500VA - IP21



SKU: 32278  
Référence technique: 29M27FDF1000



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 500 VA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP41-IK08  
Version : with electrostatic shield & regulation tabs  $\pm 5\%$   
Inrush current : less than or equal to 25 In  
Heatings : B (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 15,3 W  
Load losses : 40,3 W  
Voltage drop : 7,45 %  
UCC : 6,3 %  
Efficiency : 90 %

### DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm  
Mounting centres (a x b) : 200 x 224 mm  
Mounting diameter ( $\varnothing$ ) : 7x14 mm  
Weight : 10,1 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 1,6A  
:  
Secondary 230V (gG fuse(s)) : 4 x 1,25A  
Secondary 230V (C circuit breaker(s)) : 4 x 1,25A

### OPTIONS:

Tropicalization  
Specific colour for the enclosure