




## TPP 5000 - THREE-PHASE TRANSFORMER 400/400V - ELECTROSTATIC SHIELD - 5KVA - IP21



SKU: 31406  
Référence technique: 29B40FF00000

### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
Current : three-phase  
Certification(s) : EN 60076  
Power : 5 kVA  
Primary voltage : 400V  
Secondary voltage : 400V (Y+N)  
:  
Protection : IP21-IK08  
Version : with electrostatic shield  
Inrush current : less than or equal to 25 In  
Heatings : F (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 85 W  
Load losses : 228 W  
Voltage drop : 4,35 %  
UCC : 4,5 %  
Efficiency : 94,1 %

### DIMENSIONS:

Dimensions (A x B x H) : 380 x 370 x 530 mm  
Mounting centres (a x b) : 250 x 340 mm  
Mounting diameter (ø) : 11x22 mm  
Weight : 51 kg

### PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 16A  
:  
Secondary 400V (gG fuse(s)) : 4 x 8A  
Secondary 400V (C circuit breaker(s)) : 4 x 8A

### OPTIONS:

Tropicalization  
Specific colour for the enclosure