



TPP 5000 - THREE-PHASE TRANSFORMER 400/400V $\pm 5\%$ - 5KVA - IP21



SKU: 31407
Référence technique: 29B40FF01000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 5 kVA
Primary voltage : 400V
Secondary voltage : 400V (Y+N)
:
Protection : IP21-IK08
Version : with regulation tabs $\pm 5\%$
Inrush current : less than or equal to 25 In
Heatings : F (IEC 60085)
Max. ambient T° : 35°C
No load losses : 85 W
Load losses : 228 W
Voltage drop : 4,35 %
UCC : 4,5 %
Efficiency : 94,1 %

DIMENSIONS:

Dimensions (A x B x H) : 380 x 370 x 530 mm
Mounting centres (a x b) : 250 x 340 mm
Mounting diameter (\varnothing) : 11x22 mm
Weight : 51 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 16A
:
Secondary 400V (gG fuse(s)) : 4 x 8A
Secondary 400V (C circuit breaker(s)) : 4 x 8A

OPTIONS:

Tropicalization
Specific colour for the enclosure