




**TPP 630 - THREE-PHASE
TRANSFORMER 400/230V ±5% -
ELECTROSTATIC SHIELD - 630VA - IP21**



SKU: 32288
Référence technique: 29M28FDF1000



CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 61558-2-1
Power : 630 VA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP41-IK08
Version : with electrostatic shield & regulation tabs ±5%
Inrush current : less than or equal to 25 In
Heatings : B (IEC 60085)
Max. ambient T° : 35°C
No load losses : 17,5 W
Load losses : 43,2 W
Voltage drop : 6,4 %
UCC : 5,3 %
Efficiency : 91,2 %

DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm
Mounting centres (a x b) : 200 x 224 mm
Mounting diameter (ø) : 7x14 mm
Weight : 11,2 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 2A
:
Secondary 230V (gG fuse(s)) : 4 x 1,6A
Secondary 230V (C circuit breaker(s)) : 4 x 1,6A

OPTIONS:

Tropicalization
Specific colour for the enclosure