




**TPP 630 - THREE-PHASE  
TRANSFORMER 400/230V ±5% -  
ELECTROSTATIC SHIELD - 630VA - IP21**



SKU: 32288  
Référence technique: 29M28FDF1000



### **CARACTÉRISTIQUES TECHNIQUES:**

Type : Transformer  
Current : three-phase  
Certification(s) : EN 61558-2-1  
Power : 630 VA  
Primary voltage : 400V  
Secondary voltage : 230V (Y+N)  
:  
Protection : IP41-IK08  
Version : with electrostatic shield & regulation tabs ±5%  
Inrush current : less than or equal to 25 In  
Heatings : B (IEC 60085)  
Max. ambient T° : 35°C  
No load losses : 17,5 W  
Load losses : 43,2 W  
Voltage drop : 6,4 %  
UCC : 5,3 %  
Efficiency : 91,2 %

### **DIMENSIONS:**

Dimensions (A x B x H) : 250 x 240 x 220 mm  
Mounting centres (a x b) : 200 x 224 mm  
Mounting diameter (ø) : 7x14 mm  
Weight : 11,2 kg

### **PROTECTION(S) RECOMMANDÉE(S):**

Primary 400V (aM fuse(s)) : 3 x 2A  
:  
Secondary 230V (gG fuse(s)) : 4 x 1,6A  
Secondary 230V (C circuit breaker(s)) : 4 x 1,6A

### **OPTIONS:**

Tropicalization  
Specific colour for the enclosure