





TPP 6300 - THREE-PHASE TRANSFORMER 400/230V - ELECTROSTATIC SHIELD - 6,3KVA - IP21



SKU: 32416

Référence technique: 29B41FD01000

CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer
Current : three-phase
Certification(s) : EN 60076
Power : 6,3 kVA
Primary voltage : 400V
Secondary voltage : 230V (Y+N)
:
Protection : IP21-IK08
Version : with electrostatic shield
Inrush current : less than or equal to 25 In
Heatings : F (IEC 60085)
Max. ambient T° : 35°C
No load losses : 110 W
Load losses : 240 W
Voltage drop : 3,7 %
UCC : 3,8 %
Efficiency : 94,7 %

DIMENSIONS:

Dimensions (A x B x H) : 380 x 370 x 530 mm
Mounting centres (a x b) : 250 x 340 mm
Mounting diameter (Ø) : 11x22 mm
Weight : 59 kg

PROTECTION(S) RECOMMANDÉE(S):

Primary 400V (aM fuse(s)) : 3 x 20A
:
Secondary 230V (gG fuse(s)) : 4 x 16A
Secondary 230V (C circuit breaker(s)) : 4 x 16A

OPTIONS:

Tropicalization
Specific colour for the enclosure