




## TPP 800 - ON REQUEST THREE-PHASE TRANSFORMER 800VA - IP21



SKU: TPP800\_Specific  
 Référence technique: 29M30...



### CARACTÉRISTIQUES TECHNIQUES:

Type : Transformer  
 Current : three-phase  
 Certification(s) : EN 61558-2-1  
 Power : 800 VA  
 Primary voltage : max. 1000V  
 Secondary voltage : max. 1000V  
 :  
 Protection : IP41-IK08  
 Version : specific  
 Inrush current : less than or equal to 25 In  
 Heatings : B (IEC 60085)  
 Max. ambient T° : 35°C  
 No load losses : 22 W  
 Load losses : 59,6 W  
 Voltage drop : 6,9 %  
 UCC : 5,5 %  
 Efficiency : 90,7 %

### DIMENSIONS:

Dimensions (A x B x H) : 250 x 240 x 220 mm  
 Mounting centres (a x b) : 200 x 224 mm  
 Mounting diameter (∅) : 7x14 mm  
 Weight : 12,8 kg

### PROTECTION(S) RECOMMANDÉE(S):

:  
 Other voltages : N.C.

### OPTIONS:

Electrostatic shield  
 Thermal sensors (PTC, PT100, Twin-blades)  
 Regulation tabs  
 Primary and/or secondary coupling (star, delta, zig-zag)  
 Dual primary  
 Inrush current, frequency, heating, ambient temperature, specific altitude  
 Tropicalization  
 Specific colour for the enclosure